

1 **[0037]** CLAIM OR CLAIMS

2

3 **[0038]** What I claim as my invention is:

4 **[0039]** 1. A restraint for walking or other activity comprising:

5 (a) a primary strap of sufficient length to circle the restrainee's body and

6 long enough to be held by a guardian;

7 (b) a first secondary strap attached left of the center of the primary strap;

8 (c) a second secondary strap attached right of the center of the primary
9 strap;

10 (d) each secondary strap having a loop on the non-attached end; and

11 (e) each secondary strap being of sufficient length to pass around the
12 restrainee's body, cross, and allow the primary strap to be threaded
13 through each secondary strap loop at the restrainee's back.

14

15 **[0040]** 2) The invention as described in Claim 1 wherein:

16 (a) the primary strap is placed horizontally across the front of the
17 restrainee at the level of the axillae;

18 (b) the left secondary strap is brought over the restrainee's left shoulder
19 to the restrainee's back;

20 (c) the right secondary strap is brought over the restrainee's right
21 shoulder to the restrainee's back;

22 (d) the left and right secondary straps are crossed;

- 1 (e) the left end of the primary strap is brought under the restrainee's left
2 axilla and threaded through the loop at the end of the right secondary
3 strap;
4 (f) the right end of the primary strap is brought under the restrainee's
5 right axilla and threaded through the loop at the end of the left
6 secondary strap; and
7 (g) the ends of the primary strap being held by the guardian so as to
8 restrain the restrainee.
9

10 **[0041]** 3) The invention as described in Claim 1 wherein:

- 11 (a) the primary strap is placed horizontally across the front of the
12 restrainee at the level of the axillae;
13 (b) the left secondary strap is brought over the restrainee's left shoulder
14 to the restrainee's back;
15 (c) the right secondary strap is brought over the restrainee's right
16 shoulder to the restrainee's back;
17 (d) the left end of the primary strap is brought under the restrainee's left
18 axilla and threaded through the loop at the end of the left secondary
19 strap and then through the loop at the end of the right secondary
20 strap;
21 (e) the right end of the primary strap is brought under the restrainee's
22 right axilla and threaded through the loop at the end of the right

1 secondary strap and then through the loop at the end of the left

2 secondary strap; and

3 (f) the ends of the primary strap being held by the guardian so as to
4 restrain the restrainee.

5

6 **[0042]** 4) The invention as described in Claim 1 wherein:

7 (a) the primary strap is placed horizontally across the front of the
8 restrainee at the level of the axillae;

9 (b) the left secondary strap is brought over the restrainee's left shoulder
10 to the restrainee's back;

11 (c) the right secondary strap is brought over the restrainee's right
12 shoulder to the restrainee's back;

13 (d) the left end of the primary strap is brought under the restrainee's left
14 axilla and threaded through the loop at the end of the left secondary
15 strap;

16 (e) the right end of the primary strap is brought under the restrainee's
17 right axilla and threaded through the loop at the end of the right
18 secondary strap; and

19 (f) the ends of the primary strap being held by the guardian so as to
20 restrain the restrainee.

21

- 1 **[0043]** 5) The invention as described in Claim 1 wherein:
- 2 (a) the primary strap is placed horizontally across the front of the
- 3 restraineed at the level of the shoulders;
- 4 (b) the left secondary strap is brought under the restraineed's left axilla to
- 5 the restraineed's back;
- 6 (c) the right secondary strap is brought under the restraineed's right axilla
- 7 to the restraineed's back;
- 8 (d) the left end of the primary strap is brought over the restraineed's left
- 9 shoulder and threaded through the loop at the end of the left
- 10 secondary strap;
- 11 (e) the right end of the primary strap is brought over the restraineed's right
- 12 shoulder and threaded through the loop at the end of the right
- 13 secondary strap; and
- 14 (f) the ends of the primary strap being held by the guardian so as to
- 15 restrain the restraineed.

- 16
- 17 **[0044]** 6) The invention as described in Claim 1 wherein:
- 18 (a) the primary strap is placed horizontally across the front of the
- 19 restraineed at the level of the shoulders;
- 20 (b) the left secondary strap is brought under the restraineed's left axilla to
- 21 the restraineed's back;

- 1 (c) the right secondary strap is brought under the restrainee's right axilla
2 to the restrainee's back;
3 (d) the left end of the primary strap is brought over the restrainee's left
4 shoulder and threaded through the loop at the end of the left
5 secondary strap and then through the loop at the end of the right
6 secondary strap;
7 (e) the right end of the primary strap is brought over the restrainee's right
8 shoulder and threaded through the loop at the end of the right
9 secondary strap and then through the loop at the end of the left
10 secondary strap; and
11 (f) the ends of the primary strap being held by the guardian so as to
12 restrain the restrainee.

13
14 **[0045]** ABSTRACT OF THE DISCLOSURE

15 **[0046]** Invention restrains through the design of the harness, without the use or
16 manipulation of attached cumbersome technology. Invention is a harness of three
17 straps that is designed to easily adjust to fit the restrainee. A primary strap has two
18 secondary left and right straps each attached to the left and right of the primary strap's
19 center point. These two secondary left and right straps each have loops at their ends.
20 The primary strap is placed across the restrainee's front with the secondary left and
21 right straps brought over the shoulders (and crossed or left uncrossed) or under the
22 axillae, depending on the placement of the primary strap. The two ends of the primary

1 strap are brought through the loops of the secondary left and right straps. The ends of
2 the primary strap can be threaded through each or both loops. The guardian then
3 holds the ends of the primary strap.

4

5 **[0047] DRAWINGS**

6 **[0048]** Three pages of drawings, a total of six figures, are submitted as part of this
7 application. To more easily conform to the requirements of MPEP 608.02, *et. seq.*, the
8 drawings are submitted on separate sheets with appropriate identification for
9 submission with the application.

10 **[0049]** In order to comply with MPEP 608.01(a), applicant incorporates here in the
11 specification the three pages of drawings by reference.

12

13 **[0050] OATH OR DECLARATION**

14 **[0051]** Submitted as part of this application using Form PTO/SB/01A.

15 **[0052]** In order to comply with MPEP 608.01(a), applicant incorporates into the
16 specification here the declaration by reference.

17

18 **[0053] SEQUENCE LISTING**

19 **[0054]** Not Applicable

20